

Date Prepared: 08/05/08
Supersedes: 04/16/04
Product Name: Silencure

ChemMasters

Material Safety Data Sheet

1. Chemical Product and Company Information

Product Name: Silencure

Product Description: Silencure is a 40% Solids dual action acrylic silane concrete curing & sealing compound.

ChemMasters
300 Edwards Street
Madison, Ohio 44057
440/428-2105

In Case of Emergency Contact:
CHEMTREC 800/424-9300

2. Hazards Identification

CAUTION, Flash Point 105 °F

COMBUSTIBLE LIQUID

Causes eye, skin and lung irritation

Harmful if inhaled

Harmful if swallowed

WHMIS Classification: Class D2B & B3 (Toxic & Flammable)

Symbol: Stylized T & Flammable

Potential Health Hazards - Acute

Eye: May cause eye irritation. Direct contact with the liquid or exposure to its vapors may cause burning, tearing and redness.

Skin: May cause irritation. Prolonged or repeated exposure may cause redness and burning, drying and cracking of the skin and dermatitis. Persons with preexisting skin disorders may be more susceptible to the effects of this material.

Inhalation: Excessive concentrations of vapors or mists may cause irritation of the nose and throat and signs of nervous system depression. Persons with impaired lung function or asthma like conditions may experience additional breathing difficulties due to the irritating properties of this material.

Ingestion: Liquid is moderately toxic and may be harmful if swallowed; may produce CNS depression. May result in vomiting. Aspiration of vomitus into the lungs must be avoided as even small quantities may result in aspiration pneumonitis.

Potential Health Effects - Chronic

Kidney, lung and liver are probable target organs. See Section 11 for further information.

Carcinogenicity:
NO

NTP
NO

IARC Monographs
NO

OSHA Regulated

3. Composition / Information on Ingredients

Hazardous Components	CAS #	Exposure Limits		OTHER	% by Wt
		OSHA(PEL/TWA)	ACGIH(TLV/TWA)		
Petroleum Naphtha (Aromatic)	64742-95-6	—	100 ppm	—	25-30%
Stoddard Solvent (Aliphatic)	8052-41-3	100 ppm	100 ppm	—	15-20%
1,2,4-Trimethylbenzene	95-63-6	25 ppm	25 ppm		15% max
1,3,5-Trimethylbenzene	108-67-8	25 ppm	25 ppm		3% max
Xylene	1330-20-7	100 ppm	100 ppm		2% max
Polymer Solids	Trade Secret		NonHazardous		20%
Silicone	Trade Secret				20%

Date Prepared: 08/05/08
Supersedes: 04/16/04
Product Name: Silencure

4. First Aid Measures

Eye: Immediately flush with plenty of clean water.

Skin: Remove contaminated clothing. Clean affected area(s) thoroughly with soap and water.

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

Ingestion: Seek medical attention! Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs.

SEEK MEDICAL ATTENTION IF SYMPTOMS PERSIST.

5. Fire Fighting Measures

Flash Point (method used): 105°F (TCC)

Flammable Limits (% volume in air): **Lower** = 1 **Upper** = 7

Auto Ignition Temperature: No data available

Extinguishing Media: Extinguish with water fog, dry chemical, CO2 or foam.

Hazard Combustion Products: Carbon dioxide, carbon monoxide and/or organic compounds

Fire Fighting Instructions: Do not enter confined fire space without full bunker gear including a positive pressure, NIOSH approved, self-contained breathing apparatus. Cool containers exposed to fire with water.

6. Accidental Release Measures

Spill: Shut off ignition sources. Absorb with inert material, then place in chemical waste container for later disposal.

7. Handling and Storage

Handling: Avoid inhalation of vapors and personal contact with product. Keep liquid away from heat, sparks and flame.

Use with adequate ventilation. "Empty" containers can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers. Do not pressurize drums to empty them.

Storage: Store containers tightly closed with adequate ventilation in a cool, dry area.

8. Exposure Controls / Personal Protection

Exposure Controls: Mechanical and local exhaust should be used for indoor use.

Personal Protection: Protective clothing, goggles, neoprene gloves and a vapor respirator when TLV is exceeded.

9. Physical and Chemical Properties

Appearance: Clear liquid of low viscosity

Odor: Aromatic solvent odor

VOC Content: 516 gm/L (4.3 lbs./gal)

Boiling Point: 300-355°F

Melting Point: Not applicable

Vapor Pressure (mm/Hg): 10.3 @ 100°F

Vapor Density (Air = 1): 4.3

Solubility in Water: Negligible (<5%)

Specific Gravity (H2O = 1): 0.86

Evaporation Rate (n-Butyl Acetate = 1): 0.1

Date Prepared: 08/05/08
Supersedes: 04/16/04
Product Name: Silencure

10. Stability and Reactivity

Chemical Stability: Stable

Conditions to Avoid: Heat, sparks and flame

Incompatibility (materials to avoid): Strong oxidizing agents. Strong acids, bases and select amines.

Hazardous Decomposition or By-products: Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide and/or unidentified organic compounds.

Hazardous Polymerization: Will not occur

11. Toxicological Information

Rats exposed for 4 months to 1700 ppm of a similar solvent showed evidence of mild damage to the liver, lungs and kidneys. These effects were not seen in rats exposed for 1 year at 350 ppm. Rats exposed during pregnancy showed embryo/fetotoxic toxicity. Petroleum Naphtha may contain small percentages of Xylene. Xylene in high concentrations has resulted in hearing loss in laboratory rats.

Components	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 (rat)
Petroleum Naphtha (Aromatic)	4.7 g/kg	—	>3670 ppm/8 hours

12. Ecological Information

CWA considers petroleum distillates an oil under Section 311. Spills into or leading to surface waters that cause a sheen must be reported to the National Response Center.

13. Disposal Considerations

Dispose of in accordance with all federal, state, and local regulations. If uncertain of local requirements, contact the proper environmental authorities for information on waste disposal in your area.
Under RCRA 40 CFR 261 this material is hazardous waste number D001.

14. Transportation Information

For U S National Shipments \leq 119 gal containers: Not Regulated by DOT

For U S National Shipments $>$ 119 gal containers:

Shipping Description: Paint, Combustible Liquid, UN1263, III

Hazard Class: Combustible Liquid

For International, Vessel and Air Shipments:Paint, 3, UN1263, III

Hazard Class: Flammable Liquid

Emergency Response Guide Number: 128

Date Prepared: 08/05/08
 Supersedes: 04/16/04
 Product Name: Silencure

15. Regulatory Information

OSHA: This material is hazardous by definition of Hazardous Communications Standard (29 CFR 1910.1200)

CERCLA Reportable Quantity: Xylene RQ 100 pounds, or 5,000 pounds of this product. CWA considers petroleum distillates an oil under Section 311. Spills into or leading to surface waters that cause a sheen must be reported to the National Response Center.

SARA Title III:

Section 311/312 hazard categories: acute health, delayed health, fire

Section 313 reportable ingredients:

Components	CAS #	Maximum %
1, 2, 4 Trimethylbenzene	95-63-6	15 %
Xylene	1330-20-7	2%

16. Other Information

MSDS Status: Revised GHS Format, 8/5/08
 Industrial Abbreviation Legend listed below.

Industrial Abbreviation Legend

ACGIH	American Conference of Governmental Industrial Hygienists	mg/m ³	milligrams per cubic meter
CAA	Clean Air Act (EPA)	NIOSH	National Institute for Occupational Safety and Health
CERCLA	Comprehensive Environmental Response, Compensation & Liability Act of 1980 (Superfund) (EPA)	NTP	National Toxicology Program
CNS	Central Nervous System	OSHA	Occupational Safety and Health Administration
CWA	Clean Water Act (EPA)	PEL	Permissible Exposure Limit
DOT	Department of Transportation	ppm	parts per million
EPA	Environmental Protection Agency	RCRA	Resource Conservation and Recovery Act (EPA)
g/kg	grams per kilogram	SARA	EPA's Superfund Amendment and Reauthorization Act (EPA)
IARC	Internal Agency for Research on Cancer	STEL	Short-Term Exposure Limit, ACGIH terminology
LC50	Lethal Concentration in which 50% of the test animals are expected to die	TLV	Threshold Limit Value
LD50	Lethal Dose in which 50% of the test animals are expected to die	TWA	Time-Weighted Average

THIS PRODUCT IS FORMULATED AND LABELED FOR INDUSTRIAL AND COMMERCIAL APPLICATION ONLY

The information contained herein is given in good faith and based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. The Spray-Cure Company assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.