

**EUCOLASTIC I GUN GRADE GRAY 2 GAL MTO**Version 1.3
REVISION DATE: 08/02/2007

Print Date 08/04/2007

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : EUCOLASTIC I GUN GRADE GRAY 2 GAL MTO
Product code : 273C 02

COMPANY : Euclid Chemical Company
19218 Redwood Road
Cleveland, OH 44110

Telephone : 1-800-321-7628
Emergency Phone: : U.S. only: 1-800-255-3924
International Users Call Collect: 1-813-248-0585

Product use : Sealant

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

Gray. Non-sag gunnable paste. May cause slight irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. May cause allergic respiratory sensitization. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause slight irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. May cause allergic respiratory sensitization.

Eyes : Direct contact may cause mild irritation.

Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause sensitization resulting in irritation, itching and redness.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Overexposure may cause dermatitis, asthma, skin and respiratory sensitization and decreased lung function. Prolonged or repeated contact/exposure to aromatic petroleum distillates may cause defatting, drying, and irritation of the skin, dermatitis, and central nervous system (CNS) effects. Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. A long-term NTP study showed that oral exposure to toluene diisocyanate (TDI) caused cancer in rats and mice. A lifetime inhalation study sponsored by the International Isocyanate Institute did not show carcinogenic activity in rats. May cause allergic skin and respiratory sensitization. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Skin, Eye, Ingestion, Lung

**EUCOLASTIC I GUN GRADE GRAY 2 GAL MTO**

Version 1.3

Print Date 08/04/2007

REVISION DATE: 08/02/2007

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Aromatic Polyisocyanate Resin	NJ TSRN# 51721300-5270P	30.0 - 60.0
Diisodecyl phthalate	26761-40-0	10.0 - 30.0
Calcium Carbonate (Limestone)	1317-65-3	10.0 - 30.0
Tackifier	NJ TSRN# 51721300-5272P	5.0 - 10.0
Aromatic petroleum distillates	64742-95-6	5.0 - 10.0
Thickener	NJ TSRN# 51721300-5300P	3.0 - 7.0
Trimethyl benzene (mixed isomers)	25551-13-7	3.0 - 7.0
Titanium dioxide	13463-67-7	3.0 - 7.0
Butyl benzyl phthalate	85-68-7	- <1.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	- <1.0
2,4-Toluene diisocyanate	584-84-9	- <1.0
Toluene-2,6-Diisocyanate	91-08-7	- <0.1
o-Cresol	95-48-7	- <0.1

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

- Flash point : Not available.
- Method : Not available.
- Burning rate : Non-flammable solid
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Carbon monoxide and carbon dioxide can form. Hydrocyanic acid and nitrogen oxides can form.

**EUCOLASTIC I GUN GRADE GRAY 2 GAL MTO**

Version 1.3

Print Date 08/04/2007

REVISION DATE: 08/02/2007

Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion and contact with skin, eyes and clothing. Preferably use entire contents in one continuous work session. Do not smoke, weld, generate sparks, or use flame near container. Change soiled work clothes frequently. Clean hands thoroughly after handling. Do not store or use near food. Keep container closed when not in use. Since emptied containers retain product residue and vapor, observe precautions even after container is emptied. Store under dry warehouse conditions away from heat and all ignition sources.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**Personal protection equipment**

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Use safety glasses if eye contact is likely.
- Skin and body protection : Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use general ventilation and/ or local exhaust to reduce the airborne contaminant concentration below the exposure limit listed in the MSDS

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Calcium Carbonate (Limestone)	1317-65-3	OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		ACGIH TWA:	3 mg/m3	Respirable particles.
		ACGIH TWA:	10 mg/m3	Inhalable particles.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Trimethyl benzene (mixed isomers)	25551-13-7	ACGIH TWA:	25 ppm	

**EUCOLASTIC I GUN GRADE GRAY 2 GAL MTO**

Version 1.3

Print Date 08/04/2007

REVISION DATE: 08/02/2007

Chemical Name	CAS Number	Regulation	Limit	Form
Titanium dioxide	13463-67-7	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	10 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3	Total dust. Total dust. Respirable fraction.
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3 0.025 mg/m3	Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction.
2,4-Toluene diisocyanate	584-84-9	ACGIH TWA: ACGIH STEL:	0.005 ppm 0.02 ppm	
Toluene-2,6-Diisocyanate	91-08-7	ACGIH TWA: ACGIH STEL:	0.005 ppm 0.02 ppm	
o-Cresol	95-48-7	ACGIH TWA: OSHA PEL:	5 ppm 22 mg/m3	

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form	: Non-sag gunnable paste
Color	: Gray
Odor	: Aromatic Solvent
pH	: Not available.
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: Not available.
Water solubility	: Insoluble
Specific Gravity	: 1.3
% Volatile Weight	: 8.7 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid	: Amines. Water or moisture and oxidizing agents. Alcohols. Strong acids. Strong bases.
Stability	: Material is stable under normal storage, handling, and use.
Hazardous polymerization	: Will not occur.

**EUCOLASTIC I GUN GRADE GRAY 2 GAL MTO**Version 1.3
REVISION DATE: 08/02/2007

Print Date 08/04/2007

SECTION 11 - TOXICOLOGICAL INFORMATION

Trimethyl benzene (mixed isomers), CAS-No.: 25551-13-7
Acute oral toxicity (LD-50 oral) 8,970 mg/kg (Rat)

Butyl benzyl phthalate, CAS-No.: 85-68-7
Acute oral toxicity (LD-50 oral) 13,500 mg/kg (Rat)

2,4-Toluene diisocyanate, CAS-No.: 584-84-9
Acute oral toxicity (LD-50 oral) 5,800 mg/kg (Rat)
Acute inhalation toxicity (LC-50) 14 mg/l for 4 h (Rat) 10 mg/l for 4 h (Mouse) 13 mg/l for 4 h (Guinea pig) 11 mg/l for 4 h (Rabbit)

o-Cresol, CAS-No.: 95-48-7
Acute oral toxicity (LD-50 oral) 940 mg/kg (Rabbit) 1,800 mg/kg (Rabbit) 121 mg/kg (Rat) 344 mg/kg (Mouse) 1,350 mg/kg (Rat)
Acute inhalation toxicity (LC-50) 0.179 mg/l for 2 h (Mouse)
Acute dermal toxicity (LD-50 dermal) 620 mg/kg (Rat) 890 mg/kg (Rabbit) 620 mg/kg (Mouse)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Dispose of in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATATDG / DOT Shipping Description:
NOT REGULATED**SECTION 15 - REGULATORY INFORMATION****North American Inventories:**All components are listed or exempt from the TSCA inventory.
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.**U.S. Federal Regulations:**

SARA 313 Components : 2,4-Toluene diisocyanate 584-84-9

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard

OSHA Hazardous Components :



EUCOLASTIC I GUN GRADE GRAY 2 GAL MTO

Version 1.3

Print Date 08/04/2007

REVISION DATE: 08/02/2007

Calcium Carbonate (Limestone)	1317-65-3
Trimethyl benzene (mixed isomers)	25551-13-7
Titanium dioxide	13463-67-7
Butyl benzyl phthalate	85-68-7
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
2,4-Toluene diisocyanate	584-84-9
Toluene-2,6-Diisocyanate	91-08-7
o-Cresol	95-48-7

OSHA Status: Considered : Irritant
 hazardous based on the : Sensitizer
 following criteria: : Carcinogen

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 114 g/l
 exempt solvent)
 VOC Method 310 : 8 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Butyl benzyl phthalate	85-68-7
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7

U.S. State Regulations:

MASS RTK Components	:	Calcium Carbonate (Limestone)	1317-65-3
		Trimethyl benzene (mixed isomers)	25551-13-7
		Titanium dioxide	13463-67-7
		Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
		2,4-Toluene diisocyanate	584-84-9
		Toluene-2,6-Diisocyanate	91-08-7
		o-Cresol	95-48-7

Penn RTK Components	:	Aromatic Polyisocyanate Resin	NJ TSRN# 51721300-5270P
		Diisodecyl phthalate	26761-40-0
		Calcium Carbonate (Limestone)	1317-65-3
		Tackifier	NJ TSRN# 51721300-5272P
		Aromatic petroleum distillates	64742-95-6
		Thickener	NJ TSRN# 51721300-5300P
		Trimethyl benzene (mixed isomers)	25551-13-7
		Titanium dioxide	13463-67-7
		2,4-Toluene diisocyanate	584-84-9

NJ RTK Components	:	Aromatic Polyisocyanate Resin	NJ TSRN# 51721300-5270P
		Diisodecyl phthalate	26761-40-0
		Calcium Carbonate (Limestone)	1317-65-3
		Tackifier	NJ TSRN# 51721300-5272P
		Aromatic petroleum distillates	64742-95-6
		Trimethyl benzene (mixed isomers)	25551-13-7
		Titanium dioxide	13463-67-7
		Butyl benzyl phthalate	85-68-7
		Crystalline Silica (Quartz)/ Silica Sand	14808-60-7

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:



EUCOLASTIC I GUN GRADE GRAY 2 GAL MTO

Version 1.3
 REVISION DATE: 08/02/2007

Print Date 08/04/2007

- | | |
|------------|--|
| 85-68-7 | Butyl benzyl phthalate |
| 14808-60-7 | Crystalline Silica (Quartz)/ Silica Sand |
| 584-84-9 | 2,4-Toluene diisocyanate |
| 1333-86-4 | Carbon Black |
| 91-08-7 | Toluene-2,6-Diisocyanate |
| 100-41-4 | Ethylbenzene |
| 91-20-3 | Naphthalene |

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	2
Flammability	1
Reactivity	1
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

- | | |
|--|--|
| ACGIH - American Conference of Governmental Hygienists | PEL - Permissible Exposure Limit |
| CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act | RCRA - Resource Conservation and Recovery Act |
| DOT - Department of Transportation | RTK - Right To Know |
| DSL - Domestic Substance List | SARA - Superfund Amendments and Reauthorization Act |
| EPA - Environmental Protection Agency | STEL - Short Term Exposure Limit |
| HMIS - Hazardous Materials Information System | TLV - Threshold Limit Value |
| IARC - International Agency for Research on Cancer | TSCA - Toxic Substances Control Act |
| MSHA - Mine Safety Health Administration | TWA - Time Weighted Average |
| NDSL - Non-Domestic Substance List | V - Volume |
| NIOSH - National Institute for Occupational Safety and Health | VOC - Volatile Organic Compound |
| NTP - National Toxicology Program | WHMIS - Workplace Hazardous Materials Information System |
| OSHA - Occupational Safety and Health Administration | |