

**EUCOLASTIC I POURABLE GRAY 2 GAL**

Version 1.1

Print Date 08/01/2007

REVISION DATE: 07/31/2007

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : EUCOLASTIC I POURABLE GRAY 2 GAL  
 Product code : 173C 02

COMPANY : Euclid Chemical Company  
 19218 Redwood Road  
 Cleveland, OH 44110

Telephone : 1-800-321-7628  
 Emergency Phone: : U.S. only: 1-800-255-3924  
 International Users Call Collect: 1-813-248-0585

Product use : Coating

**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Gray. Liquid. May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization.

Eyes : Vapor and/or mist may cause eye irritation.

Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause sensitization resulting in irritation, itching and redness.

**Aggravated Medical Conditions**

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Overexposure may cause dermatitis, asthma, skin and respiratory sensitization and decreased lung function. Repeated overexposure to vapors and/or material may injure the liver, kidneys and respiratory system unless suitable engineering controls and/or personal protective equipment are used. Prolonged or repeated contact/exposure to aromatic petroleum distillates may cause defatting, drying, and irritation of the skin, dermatitis, and central nervous system (CNS) effects. Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. A long-term NTP study showed that oral exposure to toluene diisocyanate (TDI) caused cancer in rats and mice. A lifetime inhalation study sponsored by the International Isocyanate Institute did not show carcinogenic activity in rats. May cause allergic skin and respiratory sensitization. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**Target Organs:** Eye, Lung, Liver, Kidney, Skin, Nerve

**EUCOLASTIC I POURABLE GRAY 2 GAL**

Version 1.1

Print Date 08/01/2007

REVISION DATE: 07/31/2007

**SECTION 3 - PRODUCT COMPOSITION**

<b>Chemical Name</b>	<b>CAS-No.</b>	<b>Weight %</b>
Aromatic Polyisocyanate Resin	NJ TSRN# 51721300-5270P	40.0 - 70.0
Calcium Carbonate (Limestone)	1317-65-3	15.0 - 40.0
Clay	1332-58-7	15.0 - 40.0
Tackifier	NJ TSRN# 51721300-5272P	10.0 - 30.0
Aromatic petroleum distillates	64742-95-6	3.0 - 7.0
Titanium dioxide	13463-67-7	3.0 - 7.0
Trimethyl benzene (mixed isomers)	25551-13-7	1.0 - 5.0
Butyl benzyl phthalate	85-68-7	- <1.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	- <1.0
2,4-Toluene diisocyanate	584-84-9	- <1.0
Toluene-2,6-Diisocyanate	91-08-7	- <0.1

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

- Inhalation : Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**SECTION 5 - FIRE FIGHTING MEASURES**

- Flash point : 155 °F, 68 °C
- Method : Setaflash Closed Cup
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Carbon monoxide and carbon dioxide can form. Smoke, fumes. Hydrocyanic acid and nitrogen oxides can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).



**EUCOLASTIC I POURABLE GRAY 2 GAL**

Version 1.1

Print Date 08/01/2007

REVISION DATE: 07/31/2007

Fire and explosion conditions : Product may ignite if heated in excess of its flash point. Closed container, may burst when exposed to extreme heat. Empty containers may contain ignitable vapors. Vapors may travel to sources of ignition and flashback.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Change soiled work clothes frequently. Clean hands thoroughly after handling. Do not smoke, weld, generate sparks, or use flame near container. To prevent generation of static discharges, use bonding/grounding connection when pouring liquid. Extinguish all ignition sources including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Store under dry warehouse conditions away from heat and all ignition sources.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Personal protection equipment**

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Select positive pressure supplied air respirator (TC19C or equivalent) for isocyanates.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
Calcium Carbonate (Limestone)	1317-65-3	OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		ACGIH TWA:	3 mg/m3	Respirable particles.
		ACGIH TWA:	10 mg/m3	Inhalable particles.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.

**EUCOLASTIC I POURABLE GRAY 2 GAL**

Version 1.1

Print Date 08/01/2007

REVISION DATE: 07/31/2007

<b>Chemical Name</b>	<b>CAS Number</b>	<b>Regulation</b>	<b>Limit</b>	<b>Form</b>
Clay	1332-58-7	ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA:	2 mg/m3 15 mg/m3 5 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Total dust. Respirable fraction. Total dust. Respirable fraction.
Titanium dioxide	13463-67-7	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	10 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3	Total dust. Total dust. Respirable fraction.
Trimethyl benzene (mixed isomers)	25551-13-7	ACGIH TWA:	25 ppm	
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3 0.025 mg/m3	Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction.
2,4-Toluene diisocyanate	584-84-9	ACGIH TWA: ACGIH STEL:	0.005 ppm 0.02 ppm	
Toluene-2,6-Diisocyanate	91-08-7	ACGIH TWA: ACGIH STEL:	0.005 ppm 0.02 ppm	

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Form	: Liquid
Color	: Gray
Odor	: Aromatic
pH	: Not available.
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: 250 °F, 121 °C
Water solubility	: Negligible
Specific Gravity	: 1.32
% Volatile Weight	: 6.2 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid : Strong acids.Strong bases.Amines.Water or moisture.Alcohols.

**EUCOLASTIC I POURABLE GRAY 2 GAL**

Version 1.1

Print Date 08/01/2007

REVISION DATE: 07/31/2007

Stability : Material is stable under normal storage, handling, and use.

Hazardous polymerization : Will not occur under normal conditions.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Trimethyl benzene (mixed isomers), CAS-No.: 25551-13-7

Acute oral toxicity (LD-50 oral) 8,970 mg/kg ( Rat )

Butyl benzyl phthalate, CAS-No.: 85-68-7

Acute oral toxicity (LD-50 oral) 13,500 mg/kg ( Rat )

2,4-Toluene diisocyanate, CAS-No.: 584-84-9

Acute oral toxicity (LD-50 oral) 5,800 mg/kg ( Rat )

Acute inhalation toxicity (LC-50) 14 mg/l for 4 h ( Rat ) 10 mg/l for 4 h ( Mouse ) 13 mg/l for 4 h ( Guinea pig ) 11 mg/l for 4 h ( Rabbit )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

TDG / DOT Shipping Description:

NOT REGULATED

**SECTION 15 - REGULATORY INFORMATION****North American Inventories:**

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : 2,4-Toluene diisocyanate 584-84-9

SARA 311/312 Hazards : Acute Health Hazard  
Chronic Health Hazard  
Fire Hazard

OSHA Hazardous Components :

Calcium Carbonate (Limestone) 1317-65-3



**EUCOLASTIC I POURABLE GRAY 2 GAL**

Version 1.1

Print Date 08/01/2007

REVISION DATE: 07/31/2007

Clay	1332-58-7
Titanium dioxide	13463-67-7
Trimethyl benzene (mixed isomers)	25551-13-7
Butyl benzyl phthalate	85-68-7
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
2,4-Toluene diisocyanate	584-84-9
Toluene-2,6-Diisocyanate	91-08-7

OSHA Status: Considered : Irritant  
 hazardous based on the : Sensitizer  
 following criteria: : Carcinogen

OSHA Flammability : IIIA

Regulatory VOC (less water and : 83 g/l  
 exempt solvent)  
 VOC Method 310 : 6 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Butyl benzyl phthalate	85-68-7
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7

**U.S. State Regulations:**

MASS RTK Components	: Calcium Carbonate (Limestone)	1317-65-3
	Clay	1332-58-7
	Titanium dioxide	13463-67-7
	Trimethyl benzene (mixed isomers)	25551-13-7
	Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
	2,4-Toluene diisocyanate	584-84-9
	Toluene-2,6-Diisocyanate	91-08-7

Penn RTK Components	: Aromatic Polyisocyanate Resin	NJ TSRN# 51721300-5270P
	Calcium Carbonate (Limestone)	1317-65-3
	Clay	1332-58-7
	Tackifier	NJ TSRN# 51721300-5272P
	Aromatic petroleum distillates	64742-95-6
	Titanium dioxide	13463-67-7
	Trimethyl benzene (mixed isomers)	25551-13-7
	2,4-Toluene diisocyanate	584-84-9

NJ RTK Components	: Aromatic Polyisocyanate Resin	NJ TSRN# 51721300-5270P
	Calcium Carbonate (Limestone)	1317-65-3
	Clay	1332-58-7
	Tackifier	NJ TSRN# 51721300-5272P
	Aromatic petroleum distillates	64742-95-6
	Titanium dioxide	13463-67-7
	Trimethyl benzene (mixed isomers)	25551-13-7
	Butyl benzyl phthalate	85-68-7
	Crystalline Silica (Quartz)/ Silica Sand	14808-60-7

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:

85-68-7	Butyl benzyl phthalate
14808-60-7	Crystalline Silica (Quartz)/ Silica Sand



**EUCOLASTIC I POURABLE GRAY 2 GAL**

Version 1.1

Print Date 08/01/2007

REVISION DATE: 07/31/2007

584-84-9	2,4-Toluene diisocyanate
1333-86-4	Carbon Black
91-08-7	Toluene-2,6-Diisocyanate
100-41-4	Ethylbenzene
91-20-3	Naphthalene

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	3
Flammability	2
Reactivity	1
PPE	

0 = Minimum  
 1 = Slight  
 2 = Moderate  
 3 = Serious  
 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

ACGIH - American Conference of Governmental Hygienists  
 CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT - Department of Transportation  
 DSL - Domestic Substance List  
 EPA - Environmental Protection Agency  
 HMIS - Hazardous Materials Information System  
 IARC - International Agency for Research on Cancer  
 MSHA - Mine Safety Health Administration  
 NDSL - Non-Domestic Substance List  
 NIOSH - National Institute for Occupational Safety and Health  
 NTP - National Toxicology Program  
 OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit  
 RCRA - Resource Conservation and Recovery Act  
 RTK - Right To Know  
 SARA - Superfund Amendments and Reauthorization Act  
 STEL - Short Term Exposure Limit  
 TLV - Threshold Limit Value  
 TSCA - Toxic Substances Control Act  
 TWA - Time Weighted Average  
 V - Volume  
 VOC - Volatile Organic Compound  
 WHMIS - Workplace Hazardous Materials Information System