

MATERIAL SAFETY DATA SHEET

SECTION I – PRODUCT INFORMATION

MANUFACTURERS NAME
GARDNER – GIBSON CORPORATION

Date Revised 02/27/2009

STREET ADDRESS
4161 E. 7TH AVENUE
EMERGENCY TELEPHONE NUMBER
1-800-424-9300 **CHEMTREC**
PRODUCT CLASS
PREMIUM RUBBERIZED COATING
TRADE NAME
BLACKJACK 6080 RUBR-COAT 57

CITY, STATE, AND ZIP CODE
TAMPA, FL 33605
PRODUCT INFORMATION
1-813-248-2101
MANUFACTURES CODE IDENTIFICATION
6080-BJ

SECTION II- HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV PPM	TLV Mg/M3
PETROLEUM ASPHALT CAS # - 8052-42-4	<25%	ND	0.5
STYRENE BUTADIENE POLYMER CAS #- 9003-55-8	<25%	*	ND
WATER CAS #- 7732-18-5	<50%	*	ND

ADDITIONAL INFORMATION- * NOT HAZARDOUS ND = No Data

Hazardous Materials Identification System (HMIS)

Health
1

Flammability
0

Reactivity
0

Personal Protection
B

SECTION III – PHYSICAL DATA

BOILING RANGE: 212°F VAPOR DENSITY HEAVIER THAN AIR

EVAPORATION RATE SLOWER THAN ETHER PERCENT VOTILE BY VOLUME 60 % WEIGHT PER GALLON BY VOLUME 9.0 LBS

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY - Not Regulated

FLASH POINT- NA Water-based product

EXTINGUISHING MEDIA- CO2, FOAM, & DRY CHEMICAL

UNUSUAL FIRE AND EXPLOSION HAZARDS- CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. PRODUCTS OF COMBUSTION MAY BE TOXIC

SPECIAL FIRE FIGHTING PROCEDURES- WEAR SELF CONTAINED BREATHING APPARATUS. WATER MAY BE USED TO COOL CLOSED CONTAINERS. HIGH PRESSURE STREAM WILL SPREAD FIRE.

SECTION V – REACTIVITY DATA

STABILITY: STABLE CONDITIONS TO AVOID: NONE
INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZERS
HAZARDOUS DECOMPOSITION PRODUCTS: BURNING DRIED FILM MAY PRODUCE OXIDES OF CARBON AND NITROGEN.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
CONDITIONS TO AVOID: NONE

SECTION VI-HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE

ACUTE: SKIN: PROLONGED REPEATED CONTACT MAY CAUSE IRRITATION. EYES: CONTACT MAY CAUSE IRRITATION, BLURRED VISION. INHALATION: EXCESSIVE BREATHING OF HIGH VAPOR CONCENTRATION CAN CAUSE NASAL AND RESPIRATORY IRRITATION, DIZZINESS, NAUSEA AND POSSIBLE UNCONSCIOUSNESS AND EVEN ASPHYXIATION. INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS, WHICH CAN BE FATAL. CARCINOGENICITY: NO. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: PRE-EXISTING LUNG AND SKIN DISORDERS. REPRODUCTIVE EFFECTS: ND. TERATOGENIC: ND. MUTAGENIC: ND.

OTHER PRECAUTIONS: **KEEP OUT OF REACH OF CHILDREN.** AVOID CONTACT WITH SKIN OR CLOTHING.

EMERGENCY FIRST AID PROCEDURE

SKIN: WASH EXPOSED AREAS WITH SOAP AND WATER. EYES: FLUSH EYES WITH COPIOUS AMOUNTS OF WATER, IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN. INHALATION: REMOVE PERSON TO FRESH AIR. IF BREATHING IS DIFFICULT ADMINISTER OXIGEN. IF BREATHING STOPS, GIVE ARTIFICIAL RESPIRATION. SEEK MEDICAL ATTENTION IMMEDIATELY. INGESTION: DO NOT INDUCE VOMITING.

SECTION VII – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SOAK UP SPILL WITH SAND OR OTHER ABSORBENT. PLACE IN CONTAINERS. WASH AREA.

WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH LOCAL, STATE OR FEDERAL REGULATIONS.

SECTION VIII – SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: USE NIOSH/MSHA APPROVED RESPIRATOR WHEN TLV IS EXCEEDED.

VENTILATION: USE WITH ADEQUATE VENTILATION.

PROTECTIVE GLOVES: RUBBER GLOVES SHOULD BE USED.

EYE PROTECTION: SAFETY GLASSES SHOULD BE USED

OTHER PROTECTIVE EQUIPMENT: N/A

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN A COOL PLACE. PROTECT FROM FREEZING. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE.

SECTION IX – REGULATORY INFORMATION

DOT CATEGORY: NOT REGULATED

TSCA STATUS: ALL CHEMICAL SUBSTANCES IN THIS PRODUCT ARE INCLUDED ON OR EXEMPTED FROM LISTING ON THE TSCA INVENTORY OF CHEMICAL SUBSTANCES.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ).
WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Read and follow label directions and information given on Material Safety Data Sheets and use care when handling or using all petroleum products.