

# Safety Data Sheet

## MasterFinish HC 48 pnk

Revision date : 2019/10/19  
Version: 9.0

Page: 1/10  
(30605693/SDS\_GEN\_CA/EN)

### 1. Identification

#### Product identifier used on the label

## MasterFinish HC 48 pnk

#### Recommended use of the chemical and restriction on use

Recommended use\*: Product for construction chemicals  
Recommended use\*: for industrial and professional users

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF Canada Inc.  
100 Milverton Drive  
Mississauga, ON L5R 4H1, CANADA

Telephone: +1 289 360-1300

#### Emergency telephone number

CHEMTREC: 1-800-424-9300  
BASF HOTLINE: (800) 454-COPE (2673)

#### Other means of identification

Chemical family: Coating

---

### 2. Hazards Identification

#### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

#### Classification of the product

Flam. Liq.	2	Flammable liquids
Skin Corr./Irrit.	2	Skin corrosion/irritation
Carc.	1A	Carcinogenicity
Repr.	2 (unborn child)	Reproductive toxicity
STOT SE	3 (Vapours may cause drowsiness and dizziness.)	Specific target organ toxicity — single exposure

# Safety Data Sheet

## MasterFinish HC 48 pnk

Revision date : 2019/10/19

Page: 2/10

Version: 9.0

(30605693/SDS\_GEN\_CA/EN)

STOT RE	2	Specific target organ toxicity — repeated exposure
Aquatic Acute	2	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

### Label elements

Pictogram:



Signal Word:

Danger

Hazard Statement:

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging the unborn child.
H350	May cause cancer.
H373	May cause damage to organs (Central nervous system) through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
H401	Toxic to aquatic life.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P201	Obtain special instructions before use.
P271	Use only outdoors or in a well-ventilated area.
P243	Take action to prevent static discharges.
P273	Avoid release to the environment.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/gas/mist/vapours.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P240	Ground and bond container and receiving equipment.
P242	Use only non-sparking tools.
P264	Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P308 + P311	IF exposed or concerned: Call a POISON CENTER or doctor/physician.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P314	Get medical advice/attention if you feel unwell.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P370 + P378	In case of fire: Use water spray, dry powder, foam or carbon dioxide for extinction.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

# Safety Data Sheet

## MasterFinish HC 48 pnk

Revision date : 2019/10/19

Version: 9.0

Page: 3/10

(30605693/SDS\_GEN\_CA/EN)

P233 Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection point.

### Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

## 3. Composition / Information on Ingredients

### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
108-88-3	>= 50.0 - < 75.0%	Toluene
67-63-0	>= 5.0 - < 7.0%	2-Propanol
14807-96-6	>= 7.0 - < 13.0%	talc
57-50-1	>= 1.0 - < 3.0%	Sucrose
1309-37-1	>= 0.5 - < 1.5%	Iron oxide
13463-67-7	>= 0.5 - < 1.5%	Titanium dioxide
14808-60-7	>= 0.0 - < 0.3%	crystalline silica

## 4. First-Aid Measures

### Description of first aid measures

#### General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

#### If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

#### If on skin:

Immediately wash thoroughly with soap and water, seek medical attention.

#### If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

#### If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

### Most important symptoms and effects, both acute and delayed

Symptoms: Additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: No applicable information available.

# Safety Data Sheet

## MasterFinish HC 48 pnk

Revision date : 2019/10/19  
Version: 9.0

Page: 4/10  
(30605693/SDS\_GEN\_CA/EN)

### Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## 5. Fire-Fighting Measures

### Extinguishing media

Suitable extinguishing media:  
foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:  
water jet

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:  
harmful vapours, nitrogen oxides, fumes/smoke, carbon black, carbon oxides  
See SDS section 10 - Stability and reactivity.

### Advice for fire-fighters

Protective equipment for fire-fighting:  
Wear a self-contained breathing apparatus.

### Further information:

The degree of risk is governed by the burning substance and the fire conditions. If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/aerosol/spray mists. Wear eye/face protection. If exposed to high vapour concentration, leave area immediately. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

### Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

### Methods and material for containment and cleaning up

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.  
For large amounts: Pump off product.

---

## 7. Handling and Storage

### Precautions for safe handling

# Safety Data Sheet

## MasterFinish HC 48 pnk

Revision date : 2019/10/19

Page: 5/10

Version: 9.0

(30605693/SDS\_GEN\_CA/EN)

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

Protection against fire and explosion:

Product is not explosive.

### Conditions for safe storage, including any incompatibilities

Observe VCI storage rules.

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

Protect from temperatures below: 0 °C

The packed product must be protected from temperatures below the indicated one.

## 8. Exposure Controls/Personal Protection

### Components with occupational exposure limits

Sucrose	OSHA PEL	PEL 15 mg/m3 Total dust ; PEL 5 mg/m3 Respirable fraction ; TWA value 15 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ;
	ACGIH TLV	TWA value 10 mg/m3 ;
2-Propanol	OSHA PEL	PEL 400 ppm 980 mg/m3 ; STEL value 500 ppm 1,225 mg/m3 ; TWA value 400 ppm 980 mg/m3 ;
	ACGIH TLV	STEL value 400 ppm ; TWA value 200 ppm ;
Toluene	OSHA PEL	TWA value 100 ppm 375 mg/m3 ; STEL value 150 ppm 560 mg/m3 ; max. conc. 500 ppm ; CLV 300 ppm ; TWA value 200 ppm ;
	ACGIH TLV	TWA value 20 ppm ;
Iron oxide	OSHA PEL	PEL 10 mg/m3 fumes/smoke ; TWA value 10 mg/m3 fumes/smoke ;
	ACGIH TLV	TWA value 5 mg/m3 Respirable fraction ;
Silicon dioxide	OSHA PEL	TWA value 6 mg/m3 ; TWA value 20 millions of particles per cubic foot of air ; TWA value 0.8 mg/m3 ; The exposure limit is calculated from the equation, $80\text{mg/m}^3 / (\% \text{SiO}_2)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits.
Titanium dioxide	OSHA PEL	PEL 15 mg/m3 Total dust ; TWA value 10 mg/m3 Total dust ;
	ACGIH TLV	TWA value 10 mg/m3 ;
talc	ACGIH TLV	TWA value 2 mg/m3 Respirable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.

# Safety Data Sheet

## MasterFinish HC 48 pnk

Revision date : 2019/10/19

Page: 6/10

Version: 9.0

(30605693/SDS\_GEN\_CA/EN)

crystalline silica	OSHA PEL	TWA value 0.05 mg/m <sup>3</sup> (Respirable dust); OSHA Action level 0.025 mg/m <sup>3</sup> (Respirable dust);
	ACGIH TLV	TWA value 0.025 mg/m <sup>3</sup> Respirable fraction ;

### Advice on system design:

No applicable information available.

### Personal protective equipment

#### Respiratory protection:

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

#### Hand protection:

Wear chemical resistant protective gloves., Manufacturer's directions for use should be observed because of great diversity of types.

#### Eye protection:

Tightly fitting safety goggles (chemical goggles).

#### Body protection:

Body protection must be chosen based on level of activity and exposure.

#### General safety and hygiene measures:

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

## 9. Physical and Chemical Properties

Form:	liquid	
Odour:	of toluene	
Odour threshold:	No applicable information available.	
Colour:	pink	
pH value:	not applicable	
Melting point:	No applicable information available.	
Boiling point:	80 °C	
Sublimation temperature:	No applicable information available.	
Flash point:	4 °C	
Flammability:	Highly flammable.	(derived from flash point)
Lower explosion limit:	1.2 %(V)	
Upper explosion limit:	12.7 %(V)	
Autoignition:	Study does not need to be conducted.	
Vapour pressure:	The product has not been tested.	
Density:	0.96 - 1.15 g/cm <sup>3</sup> ( 20 °C)	
Relative density:	No applicable information available.	
Vapour density:	Heavier than air.	
Partitioning coefficient n-octanol/water (log Pow):	not applicable	

# Safety Data Sheet

## MasterFinish HC 48 pnk

Revision date : 2019/10/19

Version: 9.0

Page: 7/10

(30605693/SDS\_GEN\_CA/EN)

---

Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:	No applicable information available.
Viscosity, kinematic:	62 - 66 mm <sup>2</sup> /s
Solubility in water:	insoluble
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Evaporation rate:	No applicable information available.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

---

## 10. Stability and Reactivity

### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

### Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

### Conditions to avoid

See SDS section 7 - Handling and storage.

### Incompatible materials

strong acids, strong bases, strong oxidizing agents, strong reducing agents

### Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

---

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: No applicable information available.

#### Assessment other acute effects

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

# Safety Data Sheet

## MasterFinish HC 48 pnk

Revision date : 2019/10/19  
Version: 9.0

Page: 8/10  
(30605693/SDS\_GEN\_CA/EN)

### Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation.

### Sensitization

Assessment of sensitization: Based on available Data, the classification criteria are not met.

### Aspiration Hazard

No aspiration hazard expected.

## Chronic Toxicity/Effects

### Repeated dose toxicity

Assessment of repeated dose toxicity: May cause central nervous system effects.

### Genetic toxicity

Assessment of mutagenicity: No applicable information available.

### Carcinogenicity

Assessment of carcinogenicity: May cause cancer by inhalation.

#### *Information on: Titanium dioxide*

*Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.*

#### *Information on: crystalline silica*

*Assessment of carcinogenicity: In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. In long-term animal studies in which the substance was given by inhalation in high doses, a carcinogenic effect was observed. The substance and its compounds in the form of respirable dusts/aerosols classified by the German MAK commission as a category 1 carcinogen (substances that cause cancer to humans). A carcinogenic effect cannot safely be ruled out. The inhalation uptake of the alveolar fraction of the fine dust may cause damage to the lungs. The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.  
NTP listed carcinogen  
-----*

### Reproductive toxicity

Assessment of reproduction toxicity: May cause harm to the unborn child.

### Teratogenicity

Assessment of teratogenicity: Based on available Data, the classification criteria are not met.

### Other Information

The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

## Symptoms of Exposure

Additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.



# Safety Data Sheet

## MasterFinish HC 48 pnk

Revision date : 2019/10/19  
Version: 9.0

Page: 9/10  
(30605693/SDS\_GEN\_CA/EN)

---

## 12. Ecological Information

### Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Acutely toxic for aquatic organisms. May cause long-term adverse effects in the aquatic environment.

### Persistence and degradability

Assessment biodegradation and elimination (H2O)

*Information on: Toluene*

*Readily biodegradable (according to OECD criteria).*

### Additional information

Other ecotoxicological advice:

May cause long-term adverse effects in the aquatic environment.

---

## 13. Disposal considerations

### Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Residues should be disposed of in the same manner as the substance/product. Do not discharge into drains/surface waters/groundwater.

### Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

---

## 14. Transport Information

### Land transport

TDG

Hazard class: 3  
Packing group: II  
ID number: UN 1139  
Hazard label: 3  
Proper shipping name: COATING SOLUTION

### Sea transport

IMDG

Hazard class: 3  
Packing group: II  
ID number: UN 1139  
Hazard label: 3

# Safety Data Sheet

## MasterFinish HC 48 pnk

Revision date : 2019/10/19

Page: 10/10

Version: 9.0

(30605693/SDS\_GEN\_CA/EN)

Marine pollutant: NO  
Proper shipping name: COATING SOLUTION

### Air transport

IATA/ICAO

Hazard class: 3  
Packing group: II  
ID number: UN 1139  
Hazard label: 3  
Proper shipping name: COATING SOLUTION

---

## 15. Regulatory Information

### Federal Regulations

#### Registration status:

Chemical DSL, CA released / listed

#### NFPA Hazard codes:

Health: 2 Fire: 3 Reactivity: 0 Special:

---

## 16. Other Information

### SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2019/10/19

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

END OF DATA SHEET